

Safety Data Sheet (SDS)

Section 1: Chemical Product and Company Identification

Cat# : 3511

Part Name: Flash Freeze

Supplier: Decon Laboratories Inc.

460 Glennie Circle King of Prussia, Pa 19406
SDS Telephone # (610) 755-0800

Emergency Telephone Numbers

US Chemtrec: (800) 424-9300

Canada: (703) 527-3887

Identified uses: Laboratory use

Email Contact: cveloski@deconlabs.com

Section 2: Hazards Identification:

Hazard Overview

Classification of the substance or mixture

Classification (GHS-US)

Liquified gas H280

Label elements

GHS-US labeling

Hazard pictograms (GHS-US)

Signal Word: **WARNING**



Hazard and Precautionary Statements

H223 Flammable aerosol
H280 Contains gas under pressure; may explode if heated
P410+P403 Protect from sunlight. Store in a well ventilated place
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container. Do not pierce or burn, even after use.
P412 Do not expose to temperatures exceeding 50degrees C/122 degrees F

Other hazards not contributing to the classification : Contains gas under pressure; may explode if heated. Intentional misuse and inhalation abuse may cause cardiac or central nervous systems effects.
Warning. May Cause frostbite in contact with skin.

Unknown acute toxicity (GHS-US)

No data available

Safety Data Sheet (SDS)

NFPA Rating

Hazard Ratings:

These ratings are Decon Laboratories Inc.'s own assessments of the properties of the material using the ANSI/NFPA 704 Standard. Additional information can be found by consulting in the NFPA published ratings lists (List 325 and list 49).

If no data is listed the information is not available

Health 1 Flammability 0 Reactivity 1

Section 3: Composition/ Information on ingredients

Substances

Name	Product identifier	%	Classification (GHS-US)
1,1-Difluoroethane, liquefied, under pressure (Main constituent)	(CAS No) 75-37-6	> 99	Liquefied gas, H280

Full text of H-phrases: see section 16

Mixtures

Not applicable

Section 4: First Aid Measures

Description of first aid measures

First-aid measures general	: Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with labored breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.
First-aid measures after inhalation	: Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.
First-aid measures after skin contact	: Rinse with water. In case of frostbites: Wash immediately with lots of water (15 minutes)/shower. Remove clothing while washing. Do not remove clothing if it sticks to the skin. Cover wounds with sterile bandage. Consult a doctor/medical service. If burned surface > 10%: take victim to hospital
First-aid measures after eye contact	: Rinse immediately with plenty of water for 15 minutes. Do not apply neutralizing agents. Take victim to an ophthalmologist.
First-aid measures after ingestion	: Not applicable.

Most important symptoms and effects, both acute and delays

Symptoms/injuries	: Contains refrigerated gas; may cause cryogenic burns or injury. Not expected to present a significant hazard under anticipated conditions of normal use.
Symptoms/injuries after inhalation	EXPOSURE TO HIGH CONCENTRATIONS: Dizziness. Slight irritation. Headache. Nausea. Vomiting. Coordination disorders. Disturbances of consciousness. Disturbances of heart rate.
Symptoms/injuries after skin contact	: Frostbites.
Symptoms/injuries after eye contact	: Not applicable.
Symptoms/injuries after ingestion	: Not applicable.
Chronic symptoms	: No effects known.

Indication of any immediate medical attention and special treatment needs

No additional information available

Safety Data Sheet (SDS)

Section 5: Fire-Fighting Measures

Extinguishing media

suitable extinguishing media : Water spray. BC powder. Carbon dioxide.

Unsuitable extinguishing media : No unsuitable extinguishing media known.

Special hazards arising from the substance or mixture

Fire hazard : DIRECT FIRE HAZARD. Flammable aerosol. Gas/vapor flammable with air within explosion limits. INDIRECT FIRE HAZARD. May build up electrostatic charges: risk of ignition. May be ignited by sparks. Gas/vapor spreads at floor level: ignition hazard.

Explosion hazard : DIRECT EXPLOSION HAZARD. Gas/vapor explosive with air within explosion limits. INDIRECT EXPLOSION HAZARD. Heat may cause pressure rise in tanks/drums: explosion risk. may be ignited by sparks.

Reactivity : On heating/burning: release of toxic and corrosive gases/vapor e.g.: hydrofluoric acid, carbonyl fluoride. Reacts violently with (strong) oxidizers.

Advice for firefighters

Precautionary measures fire : Exposure to fire/heat: consider evacuation.

Firefighting instructions : Cool tanks/drums with water spray/remove them into safety. Physical explosion risk: cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion. Dilute toxic gases with water spray.

Protection during firefighting : Heat/fire exposure: compressed air/oxygen apparatus.

Other information : NFPA Aerosol Level 1.

Section 6: Accidental Release measures

Personal precautions, protective equipment and emergency procedures

For non-emergency personnel
Protective equipment : Insulating gloves. Protective goggles. Protective clothing. Large spills/in enclosed spaces: compressed air apparatus. See "Material-Handling" to select protective clothing.

Emergency procedures : Keep upwind. Mark the danger area. Consider evacuation. Seal off low-lying areas. Close doors and windows of adjacent premises. Stop engines and no smoking. No naked flames or sparks. Spark- and explosion-proof appliances and lighting equipment. Avoid ingress of water in the containers. Wash contaminated clothes.

For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

Environmental precautions

Prevent entry to sewers.

Methods and material for containment and cleaning up

For containment : Contain released substance, pump into suitable containers. Consult "Material-handling" to select material of containers. Plug the leak, cut off the supply. Dam up the liquid spill. Tip the container on one side to stop the leakage. Try to reduce evaporation. Measure the concentration of the explosive gas-air mixture. Dilute/disperse combustible gas/vapor with water curtain. Provide equipment/receptacles with earthing. Do not spray water on unheated tank walls. Do not use compressed air for pumping over spills.

Safety Data Sheet (SDS)

Methods for cleaning up : Damaged/cooled tanks must be emptied. Do not use compressed air for pumping over spills. See "Material-handling" for suitable container materials. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

Reference to other sections

See Heading 8. Exposure controls and personal protection.

Section 7: Handling and Storage

Precautions for safe handling

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use.

Precautions for safe handling : Comply with the legal requirements. Clean contaminated clothing. Handle uncleaned empty containers as full ones. Thoroughly clean/dry the installation before use. Do not use compressed air for pumping over. Use spark-/explosion proof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Observe normal hygiene standards. Measure the concentration in the air regularly. Measure the oxygen concentration in the air. Work under local exhaust/ventilation.

Hygiene Measures

Do not eat, drink or smoke when using this product. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Conditions for safe storage, including any incompatibilities

Storage conditions : Level 1 Aerosol
Use proper grounding procedures to avoid static electricity.
Keep only in the original container in a cool, well ventilated place away from : Keep container closed when not in use. Keep in fireproof place. Do not expose to temperatures exceeding 50 °C/ 122 °F.

Incompatible products : Strong bases. Strong acids.

Incompatible materials : Sources of ignition. Direct sunlight. Heat sources.

Storage temperature : < 50 °C

Heat-ignition : KEEP SUBSTANCE AWAY FROM: heat sources, ignition sources.

Prohibitions on mixed storage : KEEP SUBSTANCE AWAY FROM: oxidizing agents.

Storage area : Ventilation at floor level. Fireproof storeroom. Provide for a tub to collect spills. Provide the tank with earthing. Keep out of direct sunlight. Meet the legal requirements.

Special rules on packaging : SPECIAL REQUIREMENTS: with pressure relief valve. clean. correctly label, Meet the legal requirements.

Packaging materials : SUITABLE MATERIAL: steel. stainless steel. monel steel. lead. aluminium. copper. tin.

Specific end use(s)

Follow Label Directions.

Section 8: Exposure Controls/ Personal Protection

Control parameters

Safety Data Sheet (SDS)

Exposure controls

Personal protective equipment

Local exhaust ventilation, vent hoods

: Gloves. Safety glasses. Avoid all unnecessary exposure.



Materials for protective clothing

: GIVE GOOD RESISTANCE: neoprene, butyl rubber, leather, polyethylene. PVC.

Hand protection

: Insulated gloves.

Eye protection

: Safety glasses.

Skin and body protection

: Protective clothing.

Respiratory protection

High vapor/gas concentration: self-contained respirator. Maintain oxygen levels above 19.5% in the workplace. Use supplied air respiratory protection if oxygen levels are below 19.5% or during emergency response to a release of this product. Wear appropriate mask.

Other information

: Do not eat, drink or smoke during use.

Section 9: Physical and Chemical Properties

Information on basic physical and chemical properties

Physical state : Liquid

Appearance : Liquefied Gas

Molecular mass : 66.05 g/mol

Color : Colorless.

Odor : Mild, Ether-like odor.

pH : No data available

Relative evaporation rate (butyl acetate=1) : No data available

Melting point : -117°C

Freezing point : No data available

Boiling point : -25°C

Flash point : < -50 °C

Critical temperature : 114 °C

Self ignition temperature : 455 °C

Decomposition temperature : No data available

Flammability (solid, gas) : No data available

Vapor pressure at 50°C : 11700 hPa

Critical pressure : 44960 hPa

Relative vapor density at 20 °C : 2.3 (20 °C)

Relative density : 1.0 (-27 °C)

Density : 1004 kg/m³ (-25 °C)

Safety Data Sheet (SDS)

Solubility	: Poorly soluble in water. Soluble in ethanol. Soluble in ether. Soluble in hexane. Water: 0.54 g/100ml (0 °C)
Log Pow	: 0.75 (Experimental value)
Log Kow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 0.37 Pa.s (-31°C)
Explosive properties	: No data available
Oxidizing properties	: No data available
Explosive limits	: 4 - 19 vol % 112 - 518 g/m ³

Other information

VOC content	: 0 %
Gas group	: Liquefied gas
Other properties	: Gas/vapor heavier than air at 20°C. May generate electrostatic charges.

Section 10: Stability and Reactivity:

Reactivity

On heating/burning: release of toxic and corrosive gases/vapours (hydrofluoric acid, carbon monoxide - carbon dioxide, carbonyl fluoride). Reacts with (some) acids.

Chemical stability

Stable under normal conditions.

Possibility of hazardous reactions

Not established.

Conditions to avoid

Direct sunlight. Extremely high or low temperatures. Open flame. Overheating. Heat, sparks.

Incompatible materials

Strong acids. Strong bases.

Hazardous decomposition products

Toxic fume. Carbon monoxide. Carbon dioxide.

Section 11: Toxicological Information

Information on toxicological effects

Acute toxicity : Not Classified

Safety Data Sheet (SDS)

R152a (CAS #75-37-6)	
LC50 Inhalation rat (mg/l)	176 mg/l/4h (Rat: Literature study)
LC50 inhalation rat (ppm)	437500 ppm/4h Mortality in 2/6 at 43.75% and 1/6 at 38.3%. At \geq 17.52% lethargy, laboured breathing, reduced responsiveness to sound were observed. At 6.64% only hyperaemia and shallow breathing were observed.

Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Not classified
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: Not classified based on available data, the classification criteria are not met
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified based on available data, the classification criteria are not met
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified based on available data, the classification criteria are not met
Aspiration hazard	: Not classified based on available data, the classification criteria are not met
Potential Adverse human health effects and symptoms	: Based on available data, the classification criteria are not met.
Symptoms/injuries after inhalation	: EXPOSURE TO HIGH CONCENTRATIONS: Dizziness. Slight irritation. Headache. Nausea. Vomiting. Coordination disorders. Disturbances of consciousness. Disturbances of heart rate.
Symptoms/injuries after skin contact	: Frostbites.
Symptoms/injuries after eye contact	: No data available.
Symptoms/injuries after ingestion	: Not applicable.
Chronic symptoms	: No effects known.

Section 12: Ecological Information

Toxicity

Ecology - air	: Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009). Included in the list of substances which may contribute to the greenhouse effect (Regulation (EC) No 842/2006). TA-LuftKlasse 5.2.5.
Ecology - water	: Mild water pollutant (surface water). No data available on ecotoxicity.

152a (Case #75-37-6)

Persistence and degradability	Biodegradability in water: no data available.
--------------------------------------	---

Safety Data Sheet (SDS)

Bioaccumulative potential

152a (Cas #75-37-6)

Log Pow	0.75 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Mobility in soil

No additional information available

Other adverse effects

Other information : Avoid release to the environment.

Section 13: Disposal Considerations

Waste treatment methods

Waste disposal recommendations	: Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Refer to manufacturer/supplier for information on recovery/ recycling.
Additional information	: LWCA (the Netherlands): KGA category 06. Hazardous waste according to Directive 2008/98/EC.
Ecology - waste materials	: Avoid release to the environment.

Section 14: Transportation Information

In accordance with ADR / RID / ADNR / IMDG / ICAO / IATA

US DOT (ground):	UN1030, 1,1-Difluoroethane, R152A Flammable, 2.1
ICAO/IATA (air):	UN1950, Aerosols, Flammable, 2.1, Limited Quantity
IMO/IMDG (water):	UN1950, Aerosols, Flammable, 2.1, Limited Quantity
Special Provisions:	DOT-SP 11516: In accordance with this special permit, this product is not subject to labeling requirements unless offered for transportation by air. This product is not subject to placarding requirements. Outside packaging must be marked with proper shipping description and 'DOT-SP 11516'

UN proper shipping name

DOT Proper Shipping Name : 1,1-Difluoroethane, R152A Flammable

DOT Special Provisions (49 CFR 172.102) :
DOT-SP 11516: In accordance with this special permit, this product is not subject to labeling requirements unless offered for transportation by air. This product is not subject to placarding requirements. Outside packaging must be marked with proper shipping description and 'DOT-SP 11516'

DOT Packaging Exceptions (49 CFR 173.xxx)	: 306
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 304
DOT Packaging Bulk (49 CFR 173.xxx)	: 314;315

Safety Data Sheet (SDS)

Additional information

Other information : No supplementary information available.

Overland transport

Class (ADR) : 2 - Gases

Hazard identification number (Kemler No.) : 23

Classification code (ADR) : 2F

Additional Information: TDG Canada: Decon Labs, Inc has been granted Equivalency Certificate SU 9211 (ren. 1) by the TCSS, TDGD to offer for transport by road, rail and marine.

Air transport

:
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : Forbidden
DOT Quantity Limitations Cargo aircraft only (49 : 150 kg CFR 175.75)

Section 15: Regulatory Information

US Federal regulations

152a (75-37-6)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Fire hazard Sudden release of pressure hazard Immediate (acute) health hazard

International regulations

CANADA

152a (75-37-6)	
WHMIS Classification	Class A - Compressed Gas Class B Division 1 – Flammable Aerosol

NEW ZEALAND

HSNO regulation Hazard Class: 2.1.2A UN1030, 1,1-Difluoroethane, R152A Flammable, Gases that are not otherwise hazardous

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flam. Gas 1 H220 Press. Gas

Full text of H-phrases: see section 16

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD] F+; R12 Full text of R-phrases: see section 16
15.2.2. National regulations No additional information available

Safety Data Sheet (SDS)

15.2.2. National regulations
No additional information available

US State regulations


State or local regulations U.S.
New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List
U.S. - Massachusetts - Right To Know List

Section 16: Other Information

Full text of H-phrases: see section 16:

Compressed gas	Gases under pressure Compressed gas
H280	Contains gas under pressure; may explode if heated

NFPA health hazard : 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.
NFPA fire hazard : 0 - Materials that will not burn.
NFPA reactivity : 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.



HMIS III Rating

Health : 1 Slight Hazard - Irritation or minor reversible injury possible
Flammability : 0 Minimal Hazard
Physical : 1 Slight Hazard
Personal Protection : B

Date of Issue: 06/01/2000
Date of Revision: 07/12/2016

Decon Laboratories, Inc. provides the information contained herein in good faith but makes no representation as to its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose. Decon Laboratories, Inc. makes no representations or warranties, either expressed or implied of merchantability, fitness for particular purposes with respect to the information set forth herein or to which the information refers. Accordingly, Decon Laboratories, Inc. will not be responsible for damages resulting from the use of or reliance upon this information.

End of Safety Data Sheet